



## Artikel




## DN 10-20 – Haaks model

DN	D	d2	I3	I4	I5	H1	Kvs	EAN	Artikelnr.
10	Rp3/8	R3/8	26	52	23,5	58	1,70	4024052110810	0121-01.500
15	Rp1/2	R1/2	29	58	27	58	2,44	4024052111312	0121-02.500
20	Rp3/4	R3/4	34	66	29	58	2,66	4024052111817	0121-03.500




## Haaks model

DN	D	d2	I3	I4	I5	H1	Kvs	EAN	Artikelnr.
25	Rp1	R1	40	75	30,5	73	6,60	4024052112319	0121-04.500
32	Rp1 1/4	R1 1/4	46	85	39	74	10,10	4024052112715	0121-05.500



## DN 10-20 – Recht model

DN	D	d2	I1	I2	H2	Kvs	EAN	Artikelnr.
10	Rp3/8	R3/8	59	85	56	1,70	4024052112913	0122-01.500
15	Rp1/2	R1/2	66	95	56	2,44	4024052113217	0122-02.500
20	Rp3/4	R3/4	74	106	58	2,66	4024052113316	0122-03.500



## Recht model

DN	D	d2	I1	I2	H2	Kvs	EAN	Artikelnr.
25	Rp1	R1	84	118	73	6,20	4024052113415	0122-04.500
32	Rp1 1/4	R1 1/4	95	135	74	8,90	4024052113514	0122-05.500

\*) SW1: DN 10 = 22 mm, DN 15 = 27 mm, DN 20 = 32 mm, DN 25 = 41 mm, DN 32 = 49 mm

SW2: DN 10 = 27 mm, DN 15 = 30 mm, DN 20 = 37 mm, DN 25 = 47 mm, DN 32 = 52 mm

Kvs = debiet in m<sup>3</sup>/h bij een drukverschil van 1 bar met volledig geopende afsluiter.